Model KC-6 Air Compressor

The Kahlenberg Model KC-6 Air Compressor is an extremely quiet, compact, oil-less air compressor solution designed for marine use. The KC-6 includes a 120 p.s.i. (8 bar) max compressor pump/pressure switch assembly that accepts simple connection of line voltage and 3/8" (10mm) O.D. air tubing. The KC-6 is available as a stand-alone air source or in combination with Kahlenberg air receivers and accessories in complete kits as listed below.



TECHNICAL DATA				
Continuous Duty, Vibration Isolated, Thermally Protected, Oil-less				
<u>Output:</u>	6 C.F.M. FAD @ 100 p.s.i., (170 l/m @ 8 bar)			
Max. Pressure:	120 p.s.i. (8 bar)			
Voltage Req'd:	120 VAC, 60Hz or 230 VAC, 50/60 Hz 6.8A @ 230 Volts 13A @ 120 Volts			
Max. Current:				
Enclosure:	5052 Aluminum, 316 Stainless Steel 66 lbs., (30kg) 21.25 x 21.25 x 14.31 (540 x 540 x 364mm)			
<u>Weight:</u>				
<u>Dimensions:</u>				

- Quiet Operation: 64 dB(A) @ 1 Meter
- Low Maintenance: Oil-less, Continuous Duty
- Internal Shock Mounts minimize vibration
- Simple Installation (connect line voltage and flexible air tubing)
- Complete Kits Available: Including ASME Air Tank, and accessories specifically designed for Kahlenberg Air Horn Installations conforming to IMO Requirements.

Air Receiver Kits (Tank, Tubing, Fittings, Air Gauge, Safety Valve, Regulator, Ball Valve, and Air Strainer/Moisture Trap)			
Kit Number	Air Tank	Air Tank Dimensions	For Kahlenberg Air Horn Models
M-188 Air Receiver Kit	M-188	14'' x 33'' (356 x 838mm) Horizontal	up to Model T-2
M-189 Air Receiver Kit	M-189	16'' x 38'' (406 x 965mm) Horizontal	up to Model T-3A
M-189 2X Air Receiver Kit	M-189	(2) 16" x 38" (406 x 965mm) Horizontal	up to Model KDT-123