




- Hose** : WATER HOSE
- Application** : Hoses are to be used for transportation of drinking and grey water on yachts and small craft, both suction and pressure.
- Lining** : PVC (clear, transparant)
- Reinforcement** : Steel helix wire embedded between the layers.
- Cover** : PVC (clear, transparant)
- Temperature** : Suitable for use in the range - 5 to + 65° Celsius
- STANDARDS** : Non
- APPROVED STANDARDS** : No Lloyds or RINA approval.

Code	I.D.		O.D	Steel Wire Diam.	Pitch	Working Pressure			Burst Pressure	Bending Radius	Weight	
	mm	inch				bar			bar		mm	kg/m
			@20°C	@40°C	@65°C	@65°C						
DWHOSE10A	10	3/8	16	0.8	7.1	7	5	3	9	20	0.16	0.11
DWHOSE12A	12	1/2	18	0.8	7.1	7	5	3	9	25	0.18	0.12
DWHOSE16A	16	5/8	22	0.8	7.7	6	4	2.5	7.5	35	0.23	0.15
DWHOSE19A	19	3/4	26	0.8	8.4	5	3	2	6	50	0.32	0.22
DWHOSE25A	25	1	33	1.0	9.2	5	3	2	6	60	0.53	0.36
DWHOSE28A	28	1 1/8	36	1.0	10.0	4.5	3	1.5	5	66	0.57	0.38
DWHOSE30A	30	1 3/16	38	1.2	10.4	4.5	3	1.5	4.5	70	0.60	0.40
DWHOSE32A	32	1 1/4	40	1.5	11.2	4.5	3	1.5	4.5	75	0.65	0.44
DWHOSE35A	35	1 3/8	44	1.5	11.4	4	2	1	3	80	0.73	0.49
DWHOSE38A	38	1 1/2	47	1.5	11.4	4	2	1	3	90	0.80	0.54
DWHOSE40A	40	1 9/16	49	1.5	11.7	3	1	0.7	2.1	95	0.87	0.58
DWHOSE45A	45	1 3/4	55	1.8	12.8	3	1	0.7	2.1	105	1.10	0.74
DWHOSE50A	50	2	60	1.8	14	3	1	0.7	2.1	125	1.20	0.81

Identification:

		DWHOSE I.D. 25 mm (1")	<ul style="list-style-type: none"> - 0.5 meter Mark - Hose type and dimension repeated every 0.5 meter
			Blue ribbon over full length of hose