

## Selection chart of steering pump for double cylinder system

Hydraulic steering systems for inboard engine boats

Number of turns lock to lock of steering wheel as per pump & cylinder selection		Type of pumps				
		06.02.0024 40 CT with lock valve	06.02.0025 70 CT with lock valve	06.02.0015 105 CT without lock valve	06.02.0016 150 CT without lock valve	06.02.0017 200 CT without lock valve
Type of cylinders	06.01.0070 BV32T 105 kpm 759 ft.lb., 1029 Nm	6				
	06.01.0071 BV40T 165 kpm 1193 ft.lb., 1618 Nm		5.5			
	06.01.0072 BV60 ST C183 407 kpm 2944 ft.lb., 3991 Nm			9		
	06.01.0073 BV60 ST C216 610 kpm 3906 ft.lb., 5295.5 Nm				8.25	
	06.01.0074 BV80 ST C155 610 kpm 4412 ft.lb., 5982 Nm					9.5
	06.01.0075 BV80 ST C183 722 kpm 5225 ft.lb., 7080 Nm					11
	06.01.0076 BV90 ST C216 1110 kpm 8028.6 ft.lb., 10885 Nm					13
	Page 426 06.01.0077 BV110 ST C216 1650 kpm 11934 ft.lb., 16181 Nm					18.75
	06.01.0078 BV110 ST C268 2050 kpm 14827.6 ft.lb., 20103.6 Nm					23.25
	06.01.0079 BV120 ST 268 2495 kpm 18046 ft.lb., 24467.5 Nm					28